



A DIVISION OF ITW

ENGRAVED STEEL TYPEWHEELS

All Kingsley typewheels have forty characters (letters A-Z, Numbers 0-9 and special characters: left arrow, right arrow, hyphen, and blank). Typewheel machines mark one line of type. Typewheel selection for wire is insulation O.D. dependent, with the VW-026K wheel offering the broadest operating range. Curved face typewheels are available in vertical reading (top to bottom) and horizontal reading (left to right) formats.

WIRE MARKING TYPEWHEELS

(for use with Models E302, SL-14, and Autowire-23 series machines, KIP-20, and Modprints)

Curved Face, Vertical

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
VW-026K	0.068"	0.100"	.038"-.175"

Curved Face, Horizontal

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
DW-28K	0.042"	0.100"	.050" - .075"
RW-38K	0.050"	0.100"	.068" - .096"
SW-55K	0.082"	0.100"	.096" - .166"
LW-125K	0.098"	0.100"	.166" - .350"

Flat Face, Horizontal

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
FF-332K	3/32"	0.100"	0.310" - 0.400"
FF-125K	1/4"	0.100"	0.400" and > Custom

*Wire insulation O.D. range specified is for PVC insulation. Harder insulation reduces this range.

Please contact our Customer Service Department for current pricing.

2538 Wisconsin Avenue
Downers Grove, IL 60515 USA

www.itwnorwood.com
info@itwnorwood.com

Phone: 630-968-0646
Fax: 630-968-7672